Antik Nano

NEW Low-cost Multicast / OTT / Hospitality HD IP Set-Top Box

Antik Nano is ultra low-cost IPTV set-top box based on STi Liege chipset in miniature design, which can fit to your hand. It's ultra cost-effective solution because of higher perfomance and low power features. Device in tiny design and unbeatable price with enhanced video decoding perfomance supports dual H.264 HD decoding (2 x HP @L4.1, 1080i/720p). It allows HD web content video decoding including DivX and MP4pt2 to 1080p30 and 3DTV decoding with HDMI1.4b support.



Inputs / Outputs

- HDMI 1.4
- TOSLINK Digital Audio interface
- USB 2.0
- RJ45 (Ethernet 10/100BaseTX)
- 3,5 mm jack suitable for SCART or RCA adapter
- WiFi client embedded 802.11b/g/n, up to 300mbps (2T2R)
- External IR input

Key Features

- Enhanced Host CPU performance (1200DMIPS)
- Faster DDR performance with DDR3 support
- Dual H264 HD decoding
- 3DTV decoding and display capability compatible with HDMI1.4b
- Low power on standby
- Wake on HDMI CEC, IR/UHF RC input





WiFi serves as alternate internet connection method in OTT mode or in closed network it can serve as second STB network adapter to connect to home network resources (DLNA server, Bittorrent server) while wired ethernet i sused to deliver multicast to the box.

Antik Nano Specifications

Other Features

- FullHD (1080p) video support and crystal clear digital audio
- Interactive TV Support Multicast TV, Electronic Program Guide, VOD, Mozaic
- PVR and Network PVR support
- Major DRM systems integrated
- Segment streaming and buffering for OTT delivery even in low-speed networks
- Hybrid broadcast-broadband TV (HbbTV) support (optional)
- Hardware generated Picture-in-Picture
- Intelligent low power consumption management
- Optional internal Wi-Fi

CAS / SCRAMBLING / DRM

- Verimatrix
- Key Rider
- Securemedia

Accessories (optional)

- Remote control
- RCA/SCART cable
- Ethernet Cable
- HDMI cable
- Full size/Compact Keyboard
- WiFi Adapter
- Antik TV Anywhere Personal H.264 Transcoder
- IR extender cable

											1	V	/i	İ	C	1	е	•(0)										

- MPEG-2
- H.264 (AVC)
- VC-1 (WMV9)
- MPEG-4 part 2 (DivX, XviD)
- Flash (VP6, Sorenson)

Audio

- MPEG-1 (layer I/II)
- MP3
- Dolby Digital (AC-3)
- AAC (HE-AAC v2 Profile)
- FLAC
- Vorbis

Software integration

- -• Operating system Linux 2.6
- Copy Protection HDCP v 1.2 (optional)
- Ekioh (SVG), Webkit (HTML5)

Technical Specifications

- Width x depth x height 115 x 115 x 32 (mm) (without packaging)
- Weight 180g (without accessories and packaging)
- 12V/1A (external power supply adapter 100-240V, 50/60Hz)

Streaming

- MPEG-2 transport stream
- Multicast or Unicast
- TS over UDP
- TS over RTP
- HTTP streaming
- RTSP (with trick play support) for VoD
- Teletext and subtitles
- IGMP v2 & v3
- HIS

CPU & Memory

- DRAM 256 MB DDR3
- Flash 512 MB

Middleware

 ANTIK Built-in Middleware (optional)

Application

- Public internet TV
- OTT IPTV
- Digital Signage

Networking

- L2 switch
- support hybrid VLANs

- CPU STiH 206 (Liege) 650MHz, 1200 DMIPS

#