

IP POE Powered Ceiling Speaker FIP-901POE



Description:

The IP POE Powered Ceiling Speaker is the latest in IP technology. This Power over Ethernet (Compatible with both IEEE 802.3af & IEEE 802.3at) VoIP mass notification device has network-controlled speaker volume, scheduled program broadcast, priority-based multicast streaming, group definition, working status supervision, remote online technical support and trouble shoot. The speaker is capable of broadcasting audio through multicast.

The POE powered ceiling speaker enable to be built up an IP based sound system through a single CAT5 or CAT6 wire. The single CAT5 cable is used for control data, signal data and power supply, by this way, the layout cost will be much decreased without any consideration of AC nor DC power supply.

The POE powered ceiling speaker is compatible with universal POE switch, thus the POE speaker works with existing POE LAN/WAN & internet network and fiber-optical cable, no need dedicated network to be built-up. So it is very useful for office, hotel, school, bank, factory & shopping mall where POE network is already there.

The POE ceiling speaker is designed with 6" full range ceiling speaker with 15W class-D amplifier module build in, metal back cover.

Features:

- ✓ Support with existing POE switch network system
- ✓ Compatible with both IEEE 802.3af & IEEE 802.3at
- ✓ IP based POE powered 10W ceiling speaker
- ✓ Single network cable for control, signal and power supply
- ✓ Same POE speakers enable to be several group or zone defined
- ✓ Different music or voice message simultaneously broadcasted through different POE speakers.
- ✓ Paging prioritization and background music system
- ✓ Network adjustable speaker volume
- ✓ Support DHCP, no need to set IP address.
- ✓ Software support online supervision, easy to know the status of speaker

Specifications:

Model	FIP-901POE
Description	IP Based POE Ceiling Speaker
Power Output	10Watts RMS & 15W Watts Max (1KHz@-3dB)
Built-in Amplifier	15W Class D amplifier
Network I/F	10/100Mbps
Protocol	ARP, TCP/IP, UDP, ICMP & IGMP (Group Broadcast)
Audio Format	MP3/MP2
Audio Quality	16digit stereo CD level
Sampling Rate	8K~48K
Bit Rate	8K~512Kbps
Sensitivity	92dB/1W/1M
S/N Ratio	≧ 85dB
THD	≦ 0.1%
Frequency Response	100-18KHz (±3dB)
Connector	One RJ45 port for existing LAN/WAN & internet
Power Input	POE 802.3af or POE 802.3at & DC 12V
Operation Temp	-30 to 55°C
Dimension	200(Diameter)×100(Depth)mm
Cutout Size	175mm
Weight	1.2kg

System Diagram:

